

Running track surface, surface type: A – in acc. with EN 14877:2013-12

Proof of delivery
REGUPOL BSW GmbH
 Am Hilgenacker 24
 57319 Bad Berleburg (Germany)
 +49 2751 803-0
 info@regupol.de
 www.regupol.com

Item	Quantity	Scope of performance	Unit price	Total
1	m ²	<p>Lower bound base layer for synthetic surfaces, permeable to water, with increased requirements according to DIN 18035-6, made as follows:</p> <p>Asphalt type: PA 11 T WDA or PA 16 T WDA Binder type: B 70/100 Thickness: ≥ 40 mm Degree of compaction: ≥ 90 % Level tolerance under a 4 m straight edge: 4 m ≤ 8 mm Water infiltration rate: ≥ 360 mm/h</p> <p>Otherwise, the requirements according to DIN 18035-6, tables 4 and 5 apply.</p>	€	€
2	m ²	<p>Upper bound base layer for synthetic surfaces, permeable to water, with increased requirements according to DIN 18035-6, made as follows:</p> <p>Asphalt type: PA 5 D WDA or PA 8 D WDA Binder type: B 70/100 Thickness: ≥ 25 mm Degree of compaction: ≥ 90 % Level tolerance under a 4 m straight edge: 4 m ≤ 4 mm Water infiltration rate: ≥ 360 mm/h</p> <p>Otherwise, the requirements according to. DIN 18035-6, tables 4 and 5 apply.</p>	€	€
3	lfm.	<p>Make a recess, approx. 2 x 2 cm, for a frictional locking connection between the synthetic surface and adjacent components (e.g.: curb stones, drainage channels).</p> <p>The costs for the use of additional synthetic surfacing must be taken into account.</p>	€	€

Item	Quantity	Scope of performance	Unit price	Total
4	rm.	Application of adhesive tape and plastic foil to protect curb stones, drainage channels and adjoining building components from contamination by synthetic material. Removal and professional disposal after installation of the synthetic surface.	€	€
5	m ²	Professional application of adhesion promoter to the cleaned, bound base layer. Quantity: approx. 200 g/m ²	€	€
6	m ²	Delivery and professional installation of water impermeable synthetic surface in acc. with EN 14877:2013-12. Product: REGUPOL challenger PDI Surface type: A in acc. with EN 14877:2013-12 Description: Spray coated Insitu surface Base layer: Polyurethane bound rubber granules, cast. Surface thickness: approx. 11 mm Upper layer: Sprayed on polyurethane and EPDM granules. Applied amount: approx. 2.0 kg/m ² Surface: Granulate texture Colour: Red Overall thickness: approx. 13 mm	€	€

Total amount: €

Track and segment area: €