

Running track surface, surface type: E – in acc. with EN 14877:2013-12

**Proof of delivery**

**REGUPOL BSW GmbH**

Am Hilgenacker 24  
 57319 Bad Berleburg (Germany)  
 +49 2751 803-0  
 info@regupol.de  
 www.regupol.com

Item	Quantity	Scope of performance	Unit price	Total
1	m <sup>2</sup>	<p>Lower bound base layer for synthetic surfaces, impermeable to water, with increased requirements according to DIN 18035-6, made as follows:</p> <p>Asphalt type: AC 11 BN or AC 16 TL                      Binder type: B 70/100                      Thickness: ≥ 40 mm                      Degree of compaction: ≥ 95 %                      Level tolerance under a 4 m straight edge: 4 m ≤ 8 mm</p> <p>Otherwise, the requirements according to DIN 18035-6, tables 4 and 5 apply</p>	€	€
2	m <sup>2</sup>	<p>Upper bound base layer for synthetic surfaces, impermeable to water, with increased requirements according to DIN 18035-6, made as follows:</p> <p>Asphalt type: AC 5 DL or AC 8 DL                      Binder type: B 70/100                      Thickness: ≥ 25 mm                      Degree of compaction: ≥ 95 / 97 %                      Level tolerance under a 4 m straight edge: 4 m ≤ 4 mm</p> <p>Otherwise, the requirements according to DIN 18035-6, tables 4 and 5 apply.</p>	€	€
3	lfm.	<p>Application of adhesive tape and plastic foil to protect curb stones, drainage channels and adjoining building components from contamination by synthetic material. Removal and professional disposal after installation of the synthetic surface.</p>	€	€

Item	Quantity	Scope of performance	Unit price	Total
4	m <sup>2</sup>	<p>Delivery and professional installation of water impermeable synthetic surface in acc. with EN 14877:2013-12.</p> <p><b>Product:</b> <b>REGUPOL elite PUR</b></p> <p><b>Surface type:</b> E in acc. with EN 14877:2013-12</p> <p><b>Description:</b> Poured-in-place surface, multi-layer (solid synthetic surface)</p> <p><b>Base layer:</b> Poured polyurethane with interspersed rubber granules, multi-layer. Surface thickness: approx. 10 mm</p> <p><b>Upper layer:</b> Poured polyurethane with interspersed EPDM granules (grain size: 1.0-4.0 mm). Surface thickness: approx. 4 mm</p> <p><b>Surface:</b> EPDM granules with interspersed visible tips.</p> <p><b>Colour:</b> Red</p> <p><b>Overall thickness:</b> approx. 14 mm</p>	€	€

**Total amount: €**

**Track and segment area: €**