



Product Service

CERTIFICATE

No. Z2 125877 0001 Rev. 00

Holder of Certificate: **REGUPOL Germany GmbH & Co. KG**

Am Hilgenacker 24
57319 Bad Berleburg
GERMANY

Certification Mark:



Product: **Fall protection slabs**

The product was tested on a voluntary basis and complies with the essential requirements. The certification mark shown above can be affixed on the product. It is not permitted to alter the certification mark in any way. In addition, the certification holder must not transfer the certificate to third parties. This certificate is valid until the listed date, unless it is cancelled earlier. All applicable requirements of the Testing, Certification, Validation and Verification Regulations of TÜV SÜD Group have to be complied. For details see: www.tuvsud.com/ps-cert

Test report no.: 713309960-000-02

Valid until: 2029-06-09

Date, 2024-10-09

Horst Kristen

(Horst Kristen)

CERTIFICATE

No. Z2 125877 0001 Rev. 00

Model(s): FXG 50, FXG 70, FX 35, FX 50, FX 75, FX 110, FX (EPDM) 35, FX (EPDM) 50, FX (EPDM) 75, FX (EPDM) 110

Parameters:

REGUPOL PLAYFIX FXG					
Type	Length [approx. mm]	Width [approx. mm]	Thickness [approx. mm]	Weight [approx. kg/m ²]	Maximum fall height [m]
FXG 50	1000	500	50	34	1,50
FXG 70			70	46	2,00

Material: PUR binder, components made of synthetic rubber (coloured)

Connecting elements: Plug-in dowels, one-component PUR adhesive sealant

REGUPOL PLAYFIX FX					
Type	Length [approx. mm]	Width [approx. mm]	Thickness [approx. mm]	Weight [approx. kg/m ²]	Maximum fall height [m]
FX 35	1000	500	35	26	1,00
FX 50			50	29	1,50
FX 75			75	39	2,10
FX 110			110	56	3,00

Material:

Base layer: PUR binder, components made of synthetic rubber

Top layer: PUR binder, components made of synthetic rubber (coloured)

Connecting elements: Plug-in dowels, one-component PUR adhesive sealant

REGUPOL PLAYFIX FX (EPDM)					
Type	Length [approx. mm]	Width [approx. mm]	Thickness [approx. mm]	Weight [approx. kg/m ²]	Maximum fall height [m]
FX (EPDM) 35	1000	500	35	28	1,00
FX (EPDM) 50			50	35	1,50
FX (EPDM) 75			75	46	2,10
FX (EPDM) 110			110	61	3,00

Material:

Base layer: PUR binder, components made of synthetic rubber

Top layer: ethylene propylene diene (monomer) rubber used as EPDM granulate (coloured)

Connecting elements: Plug-in dowels, one-component PUR adhesive sealant

Tested according to: DIN EN 1176-1:2024 Abschnitt 6.2
DIN EN 1177:2024