PRODUCT INFORMATION



REGUPOL PLAYFIX FX (EPDM)







PRODUCT INFORMATION

REGUPOL PLAYFIX FX (EPDM)





Applications:

Swings, slides, see-ways | Climbing, jumping, gymnastics | Playing, running, chasing | Water playgrounds

Material:

Base layer: PUR binder, components made of synthetic rubber

Top layer: ethylene propylene diene (monomer) rubber used as EPDM granulate (coloured)

Maximum fall height:

up to 3.00 m, fall protection testing in acc. with DIN EN 1177

Dimensions | Weight | Maximum fall height:

1,000 x 500 x 30 mm | approx. 24 kg/m² 1,000 x 500 x 50 mm | approx. 35 kg/m² | 1.50 m 1,000 x 500 x 75 mm | approx. 46 kg/m² | 2.10 m 11,000 x 500 x 100 mm | approx. 56 kg/m² | 2.80 m 1,000 x 500 x 110 mm | approx. 61 kg/m² | 3.00 m Tolerances: length / width \pm 1 % | thickness \pm 2 mm

Structure:

Dual-layer structure, drainage grooves on the underside, (no drainage grooves for 30 mm), dummy joint on the top side

Colours:

21 EPDM granulate colours

Accessories:

Plug-in dowels, one-component PUR adhesive sealant

Special features and benefits:

Safety, certified high-quality production, no dispersal through play, weather-resistant, can be cleaned, fast installation

Service:

Product sample service, individual consulting worldwide, customized product development and design, cleaning and maintenance, repairs, re-topping and renovation

Installation:

On concrete, asphalt or compacted bed of crushed stone or gravel

Sustainability:

Our **REGUPOL playfix safety floors** have been awarded the label "Top Recycled Product" by the NEW LIFE initiative. This label is only awarded to products consisting of over 20% recycled material

Water permeability:

Water permeable

Sale and distribution:

In and outside Europe

PRODUCT INFORMATION





EPDM granulate



Deviations from the colours shown are possible due to production batches and brochure print.

Country-specific requirements must be complied with. We will be happy to advise you regarding the product you want to buy.